



Product name	:	MoTip Chrome Lacquer	
Article number	:	04060	
Supplier / Producer	:	MOTIP DUPLI B.V.	
		Wolframweg 2	
		NL-8471 XC WOLVEGA	
		Telephone number	+31 561 – 69 44 00
		Telefax number	+31 561 – 69 44 31

Product description

High quality, decorative lacquer to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic.

Product characteristics

Excellent coverage
Metallic gloss
Not rub resistant
Not resistant to weather influences
Excellent adhesion

Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Acrylic resin
Colour	:	Chrome
VOC-content	:	Approximately 90% w/w
Solid content	:	Approximately 10% w/w
Gloss	:	Metallic
Coverage	:	1,25 to 1,75 m ²
Dust dry	:	After 5 to 10 minutes
Hardened	:	After 24 hours
Heat resistant	:	To 110°C

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of MoTip primer suitable for the surface. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

Not re-sprayable with clear varnish.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.